

TECHNICAL DATA SHEET
HPL LOCKERS WITH ALUMINIUM PROFILES
V, T, M, C, P, B, Z and L SERIES





SERIES



FVP SERIES
1 door per column



FTP SERIES
2 doors per column



FMP SERIES
3 doors per column



FCP SERIES
4 doors per column



FPP SERIES
5 doors per column



FBP SERIES
6 doors per column



FZP SERIES
8 doors per column



FLP SERIES
8 doors per column



CHARACTERISTICS

Made of HPL-panels of phenolic resins.

Rigid material, water-resistant, fire-resistant, antibacterial and adequate for wet areas.

Highly resistant against wear, that is why it is ideal for applications with a high index of use and frequent cleaning.

Core of black colour.

According to the european norms EN 438-1 and EN 438-2.

Density 1450 Kg/m³ according to DIN 53479.

Water-absorption of less than 3%.

4 mm thick board on the sides, 8 mm thick on the floor and ceiling and 10 or 12 mm thick on the doors.

4 mm thick board on the back sides plus aluminium stabilising profiles.

Rounded edges.

No maintenance required.

4 mm thick grooved phenolic back panel, fully framed.

Aluminium stabilising profiles.

Slide lock with removable cylinder and master key.

Adjustable 150 mm PVC legs.

Aluminium clothes rail with two hanging hooks in a.b.s. (Models FVP and FTP).

Upper tray (Model FVP).

A2 stainless steel screws.

Numbering plates included.


Easy cleaning

The nonporous surface repels dirt. Easy cleaning of the HPL, with normal chemical detergents, or with sanitizing products, against which the material is inalterable. In case of cleaning it from graffiti it can be used an organic dissolvent without risk of alteration of the colour.


Resistant against food residuals and colourants, as they do not affect neither the properties nor the appearance of the HPL (phenolic material). The Steel wool, or similar products, are not recommended, as they can scratch the surface and create cavities of corrosión, especially at the stainless Steel components. Take special care with the use of materials which contain chlorides, as they are contraindicated, as they can caus oxidation. Hydrochloric acid or iron products in prolonged contact, are also not recommended. Never use common Steel cleaners for stainless Steel!




HPL COLOURS (DOORS)




WHITE
F-085




LIGHT GREY
F-0074



DARK BLUE
M-0717




DARK GREY
F-0077




RED
F-0210



CREAM
F-0851



YELLOW
F-0010




ORANGE
F-0011




LIGHT GREEN
F-0725




DARK GREEN
F-0591




TURQUOISE
F-0876




BURGUNDY
F-0318



LIGHT BLUE
F-0718




ALUMINIUM
F-0193



BLACK
F-0080




LIGHT WOOD
FM-100



DARK WOOD
FM-200



ASH OAK
F-3235



ROCK CEMENT
F-0026




EARTH CEMENT
F-0027




CHOCOLATE
F-0863




LOCKS



Latch bolt
For melamine doors
For HPL doors
For methacrylate doors




Padlockable Metallic Lock 2
For metal doors
For melamine doors
For HPL doors
For methacrylate doors



Metal handle
For metal doors
For melamine doors
For HPL doors
For methacrylate doors



Coin-operated Lock (coin-return)
For metal doors
For melamine doors
For HPL doors
For methacrylate doors




Coin-operated Lock + Coin Collect Box
For metal doors
For melamine doors
For HPL doors
For methacrylate doors



Lock of 4 manual digits with emergency key
For metal doors
For melamine doors
For HPL doors
For methacrylate doors



TELEC
Electronic lock combination
For metal doors
For melamine doors
For HPL doors
For methacrylate doors



PROXI
Electronic lock of proximity
For metal doors
For melamine doors
For HPL doors
For methacrylate doors



TELOCK
Electronic lock combination
For metal doors
For melamine doors
For HPL doors
For methacrylate doors




SOLOCK
Electronic lock combination
For metal doors
For melamine doors
For HPL doors
For methacrylate doors




FYLOCK
Electronic lock
For metal doors
For melamine doors
For HPL doors
For methacrylate doors



OPTIONS




Mailbox slot




Slope top
F-085 colour




Decorative end panel
The same colour as the door



Socle
F-085 colour




Centre part division
FV-40 series



Additional shelf



Door opening limiter
90°.




Elastic bracelet
With numbering option




COMBINATIONS AND DIMENSIONS


FVP SERIES




FVP-30/1
31kg . 0,28m³




FVP-30/2
55kg . 0,54m³



FVP-30/3
79kg . 0,80m³




FVP-30/4
104kg . 1,07m³



FVP-40/1
37kg . 0,37m³




FVP-40/2
66kg . 0,72m³




FVP-40/3
96kg . 1,07m³


FTP SERIES




FTP-30/1
32kg . 0,28m³




FTP-30/2
56kg . 0,54m³




FTP-30/3
81kg . 0,80m³




FTP-30/4
106kg . 1,07m³



FTP-40/1
37kg . 0,37m³



FTP-40/2
67kg . 0,72m³




FTP-40/3
97kg . 1,07m³

To the depth of the changing rooms, the thickness of the type of door chosen must be added: 10 or 2 mm thickness.




COMBINATIONS AND DIMENSIONS


FMP SERIES




FMP-30/1
34kg . 0,28m³




FMP-30/2
62kg . 0,54m³




FMP-30/3
89kg . 0,80m³




FMP-30/4
116kg . 1,07m³



FMP-40/1
40kg . 0,37m³




FMP-40/2
74kg . 0,72m³




FMP-40/3
108kg . 1,07m³


FCP SERIES




FCP-30/1
37kg . 0,28m³




FCP-30/2
67kg . 0,54m³




FCP-30/3
97kg . 0,80m³




FCP-30/4
127kg . 1,07m³



FCP-40/1
44kg . 0,37m³



FCP-40/2
81kg . 0,72m³




FCP-40/3
118kg . 1,07m³

To the depth of the changing rooms, the thickness of the type of door chosen must be added: 10 or 2 mm thickness.




COMBINATIONS AND DIMENSIONS


FPP SERIES




FPP-30/1
40kg . 0,28m³




FPP-30/2
73kg . 0,54m³




FPP-30/3
105kg . 0,80m³




FPP-30/4
138kg . 1,07m³



FPP-40/1
47kg . 0,37m³




FPP-40/2
88kg . 0,72m³




FPP-40/3
128kg . 1,07m³


FBP SERIES




FBP-30/1
42kg . 0,28m³




FBP-30/2
78kg . 0,54m³




FBP-30/3
113kg . 0,80m³




FBP-30/4
149kg . 1,07m³



FBP-40/1
51kg . 0,37m³



FBP-40/2
94kg . 0,72m³




FBP-40/3
139kg . 1,07m³

To the depth of the changing rooms, the thickness of the type of door chosen must be added: 10 or 2 mm thickness.




COMBINATIONS AND DIMENSIONS


FZP SERIES




FZP-30/1
48kg . 0,28m³




FZP-30/2
89kg . 0,54m³




FZP-30/3
129kg . 0,80m³




FZP-30/4
170kg . 1,07m³



FZP-40/1
57kg . 0,37m³




FZP-40/2
108kg . 0,72m³




FZP-40/3
159kg . 1,07m³


FLP SERIES




FLP-30/1
38kg . 0,28m³




FLP-30/2
70kg . 0,54m³




FLP-30/3
101kg . 0,80m³




FLP-30/4
132kg . 1,07m³



FLP-40/1
44kg . 0,36m³



FLP-40/2
80kg . 0,71m³



FLP-40/3
117kg . 1,05m³

To the depth of the changing rooms, the thickness of the type of door chosen must be added: 10 or 2 mm thickness.